Features and Specifications

Voltage: 120/220V 60Hz
Power consumption: 6 watts
Color temperature: 3000K
Luminosity: 325 lumens
Luminaire efficacy: 54 lumens/watt

Color rendition index: 90

Rated lifespan: 50,000 hours

Bulb type: glare free, high output LED array

Cord length: 6 feet

Table Lights

Pixo table lights feature an aluminum arm with a polycarbonate shade. The steel base has a polycarbonate cover with an integrated USB charging port. Pixo's arm rotates 360 degrees, with a 180 degree tilt. The shade, which rotates 360 degrees independently of the arm, houses a glare free, advanced LED array that eliminates multiple shadows. The optical switch offers full range dim control. An optional occupancy sensor is also available.

Additional Notes

Pixo lights ship flat-packed. Minor assembly is required.

All Pixo lighting is ETL, CE, PSE, and RoHS certified. Pixo optical switches comply with ADA.





Surfaces

Trim


Black (TR-11) Silver (TR-12) White (TR-13)

Pixo

Pablo Designs | Fernando Pardo and Pablo Pardo | 2011 | Imported from China

To order, specify:

- 1. Product number
- 2. Trim color







D: 6"	d
<u>0mm</u>	$(\cdot$

Table Light	Number	List Price
	LUPT-0016-05FLC	275.00

Table Light with Occupancy Sensor	Number	List Price
	LUPT-0016-05FLO	315.00